


CHARACTERISTICS

Nominal Voltage		12V
Nominal Capacity (20 hour rate)		9Ah
Capacity 25°C	10 hour rate (9.0A)	8.1Ah
	5 hour rate (15.9A)	7.55Ah
	1 hour rate (55.4A)	5.61Ah
Internal Resistance		Full Charged Battery 25°C ≤20mΩ
Capacity affected by Temperature (10 hour)	40°C	102%
	25°C	100%
	0°C	85%
	-15°C	65%
Self-Discharge 25°C Capacity	after 3 month storage	90%
	after 6 month storage	80%
	after 12 month storage	62%
Charge (Constant Voltage) 25°C	Float	Initial Charging Current Less than 2.55A Voltage 13.6-13.8V
	Cycle	Initial Charging Current Less than 2.55A Voltage 14.4-15.0V

PACKAGING



Battery Dimensions	Length	151mm
	Width	65mm
	Height	94mm
	Total Height	100mm
Quantity Per Box	8 pcs per box	
Net weight Per Box	19.2kg	
Gross Weight	19.8kg	



Discharge Constant Current per Cell (Amperes at 25°C)


F.V/Time	30min	1h	2h	5h	10h	20h
1.60V	9.76	5.67	3.51	1.60	0.89	0.47
1.65V	9.50	5.47	3.44	1.57	0.87	0.46
1.70V	9.24	5.28	3.38	1.54	0.86	0.45
1.75V	8.97	5.08	3.32	1.51	0.84	0.44
1.80V	8.71	4.89	3.19	1.46	0.81	0.43

PERFORMANCE CHARACTERISTICS




Temperature effect on designed float life


Float charging Voltage:
13.65±0.01V/piece at 25°C




Discharge characteristics (25°C)



Temperature effect on battery self-discharge



Temperature effect on capacity



BATTERY CONSTRUCTION								
Component	Positive plate	Negative plate	Container	Cover	Safety valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Si-Rubber	Copper	Fiberglass	Sulfuric acid