



ODYSSEY BATTERY SPECIFICATIONS

Apr-13

Code	PHCA	CCA	L	W	H	Kg	Terminal
PC310	310	100	138	86	101	2.7	M4 Female
PC535	535	200	171	100	157	5.4	M6 Stud
PC545	545	185	118	86	131.3	5.7	M6 Female
PC625	625	265	171	100	175	6	M6 Stud
PC680	680	220	185	79	169.4	7	M6 Female or SAE
PC925	925	380	169	179	128	11.8	M6 Female or SAE
PC1200	1200	550	200	170	172.7	17.4	M6 Female or SAE
PC1220	1220	470	302	175	190	20.5	M6 Female or SAE
PC1230	1230	730	241	178	202	20.6	TOP SAE / SIDE 3/8 Female
PC1350	1350	615	377	175	190	27.4	DIN SAE
PC1400/25	1400	820	241	174	221	22.7	SAE
PC1400/35	1400	820	241	174	223	22.7	SAE
PC1500	1500	880	276	172	199	22.4	SAE
PC1700	1700	875	331	169	176	27.6	M6 Female or SAE
PC1750-65	1750	930	301	183	189	26.3	SAE
PC2150	2150	1150	331	173	239	35.3	3/8 STUD or SAE
PC2250	2250	1225	286	269	233	39	Dual SAE & 3/8 Stud
Extreme 30	950	450	250	97	156	9	MB Stud
Extreme 40	1100	500	250	97	206	12.5	MB Stud

1300 769 282

www.rjbatt.com.au