



SUMMIT

Bluetooth

The newest line of chargers from Lester Electrical, the Summit Series<sup>™</sup> II charger family includes the most comprehensive feature set and best performance we have delivered in our fifty plus year history as a company. The chargers are ideal for use in any motive power application including golf cars, aerial work platforms, floor care machines, industrial vehicles, lift trucks and outdoor power equipment.



AVAILABLE MODELS

36V / 25A

48V / 22A

24V / 25A



Push charge histories to the cloud to access data anywhere in the world. Enjoy expert technical support as our Lester Electrical staff can quickly see historical charging records. Add new charging profiles to your charger by pulling from the cloud and pushing to your charger. Lester has been designing and manufacturing industrial battery chargers for more than fifty years. We are an employee owned company and every member of our team is invested in the quality we deliver our customers. Universal AC input and external DC and signal connections allow for easy customization and worldwide use. Our 1050W offers multi-voltage support allowing one charger to operate at 24V, 36V, or 48V.

## **SPECIFICATIONS**

| AC INPUT  |                                  |  |
|---|----------------------------------|--|
| Voltage range, rated                                | 100-240 Vac                      |  |
| Voltage range, operating                            | 85-265 Vac                       |  |
|   | (< 108 Vac: reduced power)       |  |
| Frequency, rated                                    | 50-60 Hz                         |  |
| Frequency, operating                                | 45-65 Hz                         |  |
| Phase   | Single-phase                     |  |
| Current, maximum                                    | < 12 A                           |  |
| Efficiency > 91% peak, CEC test procedure, 115 Vac, |                                  |  |
|   | and DC losses included           |  |
| Protection  | Current limit, surge, transient, |  |
|   | under voltage, over voltage      |  |

| DC OUTPUT             |   |        |        |  |
|-----------------------|---|--------|--------|--|
| Power                 | 1050 W  |        |        |  |
| Voltage, nominal      | 24 Vdc  | 36 Vdc | 48 Vdc |  |
| Voltage, maximum      | 36 Vdc  | 54 Vdc | 72 Vdc |  |
| Current, maximum      | 25 A  | 25 A   | 22 A   |  |
| Voltage, min start-up | 10 Vdc  |        |        |  |
| Battery types         | Lead-acid (Wet / AGM / Gel), lithium, custom          |        |        |  |
| Protection            | Current limit, short circuit, reverse polarity, under |        |        |  |
|                       | voltage, over voltage, wrong battery voltage          |        |        |  |

| ENVIRONMENTAL         |                                    |  |
|-----------------------|------------------------------------|--|
| Enclosure rating      | IP66, NEMA 4                       |  |
| Operating temperature | -25 °C to 60 °C (-13 °F to 140 °F) |  |
| Storage temperature   | -40 °C to 85 °C (-40 °F to 185 °F) |  |

## 9 1/q. 0 1/q. 0 3 1/32"



Specifications are subject to change without notice. Copyright Lester Electrical of Nebraska, Inc. All rights reserved.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc., and any use of such marks by Lester Electrical is under license. Other trademarks and trade names are those of their respective owners.

Apple is a trademark of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc., registered in the U.S. and other countries.

Android is a trademark of Google Inc. Google Play and the Google Play logo are trademarks of Google Inc.



WEBSITE: www.LesterElectrical.com PHONE: (402) 477-8988 E-MAIL: JillA@LesterElectrical.com

Lester Electrical 625 West A Street, Lincoln, NE 68522, USA

## **USER & VEHICLE INTERFACES**

| Bluetooth Wireless  | Apps for Apple and Android phones and tablets   |
|---------------------|---|
| LEDs                | Charge Complete (green), Charge<br>Status (yellow), AC Present (blue),<br>Fault (red)   |
| Lockout / interlock | Single wire   |
| Remote LEDs         | Charge Complete (green), Charge<br>Status (yellow), output and LED assembly<br>optional |

| MECHANICAL                    |   |  |
|-------------------------------|---|--|
| Dimensions (LxWxH),           | 10.969 x 9.250 x 4.000 in                 |  |
| (removable feet not included) | (279 x 235 x 102 mm)                      |  |
| Cooling                       | Natural convection (no fan)               |  |
| AC input connector            | IEC 60320 C16 inlet with cord clamp       |  |
| DC output connector           | External terminals with cover             |  |
| Lockout connector             | External terminal with cover              |  |
| Mounting                      | Shelf, wall, bulkhead, threaded rod, hook |  |
| Handle                        | Carrying handle optional                  |  |

| SAFETY/REGULATORY  |   |
|--------------------|---|
| Efficiency         | CEC Appliance Efficiency Regulations, Title 20;   |
|                    | DOE Code of Federal Regulations, 10 CFR Part 430  |
| Safety / Emissions | UL recognized/listed; cUL/CSA certified; FCC Part |
|                    | 15; ICES-003; EN safety, emissions, immunity; CE  |
|                    | Certified; ACMA RCM (C-Tick)                      |