

Technical Information

Delkor AGM batteries are engineered to support the increased electrical loads of Idle Stop Start (ISS) vehicles, providing reliable starting power in the most demanding conditions.

The AGM design coupled with patented PowerFrame® grid technology delivers the best solution for applications where superior battery life and performance is required. Can also be installed as a high performance upgrade for most LN6 flooded applications.



Features & Benefits

- Patented PowerFrame® grids extend battery life
- OE proven technology
- Designed for Idle Stop Start technology
- High charge acceptance
- High vibration resistance
- Certified non-spillable design
- Low self-discharge

Applications

Idle Stop Start vehicles

Prestige European

Premium SUV & 4x4

Technical Specifications

Battery Type	Absorbent Glass Mat	Case Material / Colour	Polypropylene / Grey
Voltage	12V	Lid Type / Colour	VRLA / Grey
Capacity (20Hr)	105Ah	Grid Type	PowerFrame® Positive & Negative Grids
CCA (-18°C, SAE)	950A	Separator Type	Absorbent Glass Mat
Reserve Capacity (25A, SAE)	190 minutes	Assembly Layout	RH Positive [- +]
		Terminal Type	SAE Std.
Overall Size (LxWxH)	393 x 175 x 190mm	Case Size	DIN LN6, DIN100H
Nominal Weight	29.4kg	Ledges	Long Side, Short Side