

Technical Information

The Delkor N150HD is an N150 size sealed maintenance free starting battery. Unlike other standard N150 sizes, the Delkor N150HD has been designed with thicker plates, and a unique plate design to specifically increase durability in severe service applications like mining, large scale earthmoving and long-haul transport. The unrivalled quality of Delkor has seen their Korean manufacturing facility awarded 1st place in the coveted Korean Excellence In Manufacturing Award for 11 consecutive years (2006-2016).



Features and Benefits

- Specially designed plates for increased durability in severe service applications
- Anti-vibration
- Calcium-Calcium Lead plates with high tin content
- Unique high density active material on plates
- Built in hydrometer
- Heat sealed leak proof cover
- Patented liquid & gas separators to prevent electrolyte loss
- Flame arrestors on vents
- Low resistance envelope separators
- High strength polypropylene case

Applications

Severe service applications
Earth Moving
Heavy Haulage
Long-Haul transport

Technical Specifications

Battery Type:	Sealed Maintenance Free	Container Material / Colour:	Polypropylene / Black
Voltage:	12V	Lid Type / Colour:	Heat Sealed / Black
Capacity (@20hr rate):	150	Plate Type:	Lead/calcium/Tin expanded metal
Cold Cranking Amps -18°C, SAE:	1050	Separator Type:	Low Resistance - Microporous Envelope
Cold Cranking Amps - 0°C SAE:		Anti-Vibration:	Yes
Reserve Capacity:	300	Assembly Layout:	RHP
Overall Dimensions:	L 507 x W 213 x H 231	Terminal Type:	SAE
Wet Battery Weight:	42.5 kg	BCI Group:	4D

WARRANTY: 12 MONTHS.

Normal Delkor commercial battery warranty conditions apply. Refer to Delkor warranty statement for more information.