Issue Date: 28/11/2017

Issued By: R & J Batteries PTY LTD



Technical Information

The Delkor 56219 is a high-quality calcium/calcium, sealed maintenance free, DIN spec battery. The superior construction qualities include the latest PowerFrame plate grid technology for significant improvements in durability and performance, vibration resistance and extremely high cranking power. The unrivalled quality of Delkor has seen their Korean manufacturing facility awarded 1st place in the coveted Korean Excellence In Manufacturing Award for 12 consecutive years (2006-2017).



Features and Benefits

- Patented PowerFrame plate construction
- Unique high density active material on plates
- Built in hydrometer
- Heat sealed leak proof cover
- Patented liquid & gas separators to prevent electrolyte loss
- Flame arrestors on vents
- Low resistance envelope separators
- High strength polypropylene case

Applications
Japanese vehicles
Australian vehicles
Korean vehicles
Thailand Vehicles
Commercial
4 x 4

Technical Specifications				
Battery Type:	Sealed Maintenance Free	Container Material / Colour:	Polypropylene / Black	
Voltage:	12 V	Lid Type / Colour:	Sealed / Black	
Capacity (@20hr rate):	65ah	Plate Type:	PowerFrame	
Cold Cranking Amps -18°C, SAE:	580	Separator Type:	Low resistant Microporous Envelope	
Cold Cranking Amps - 0°C SAE:	ТВА	Anti-Vibration:	No	
Reserve Capacity:	140 minutes	Assembly Layout:	0 (RH Positive)	
Overall Dimensions:	L 242 x W 175 x H 190	Terminal Type:	SAE	
Wet Battery Weight:	15.5kg	BCI Group:	PLN2	