

Technical Information

The Delkor 27HR680 is a Group 27 sealed maintenance free starting battery. The Superior construction qualities include the latest PowerFrame plate technology which provides significant improvements in strength, performance and life span. The unrivalled quality of Delkor has seen their Korean manufacturing facility awarded 1st place in the coveted Korean Excellence In Manufacturing Award for 11 consecutive years (2006-2016).

The Delkor 27HR680 is designed to provide years of reliable, trouble free and maintenance free starting for a wide variety of applications including light commercial vehicles, farming and agricultural equipment, 4x4, passenger cars and earthmoving equipment.



Features and Benefits

- Patented PowerFrame plate construction
- Unique high density active material on plates
- Built in hydrometer
- Heat sealed leak proof cover
- Patented liquid & gas separators to prevent electrolyte loss
- Flame arrestors on vents
- Low resistance envelope separators
- High strength polypropylene case

Applications

Agricultural machinery
Earth Moving Equipment
Light commercial equipment
Passenger cars
4x4

Technical Specifications

Battery Type:	Sealed Maintenance Free	Container Material / Colour:	Polypropylene / Black
Voltage:	12 V	Lid Type / Colour:	Sealed / Black
Capacity (@20hr rate):	90	Plate Type:	PowerFrame
Cold Cranking Amps -18°C, SAE:	680	Separator Type:	Low Resistance - Microporous Envelope
Reserve Capacity:	160 minutes	Assembly Layout:	0 (RH Positive)
Overall Dimensions:	L 306 x W 173 x H 225	Terminal Type:	SAE
Wet Battery Weight:	21 kg	BCI Group:	Group 27